

Mounting Depths Requirements

				Motorized - No Valance		Motorized - Cassette Valance	
	No Valance	Standard Valance	Cassette Valance	Standard Battery	Satellite Battery	Standard Battery	Satellite Battery
Minimum Installation Depth	1-1/2"	1-1/2"	2-1/8"	N/A	1-1/2"	3"	2-1/8"
Flush Mount Installation Depth*	2-1/2"	3-1/4"	Med. 3" Lg. 3-5/8"	N/A	2-1/2"	4-1/4"	3"
Maximum Fabric Width Deduction	1-1/4"	1-1/4"	1-1/2"	1-1/4"	1-1/4"	1-1/2"	1-1/2"
Width Tolerance	1/16"	1/16"	1/16"	1/16"	1/16"	1/16"	1/16"
Height Tolerance	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Valance Height	N/A	3-1/2"	Med. - 3" Lg. - 3-1/2"	N/A	N/A	Med. - 3" Lg. - 3-1/2"	Med. - 3" Lg. - 3-1/2"
Extension Bracket Projection	1-1/8"	1-1/8"	3"	N/A	N/A	3"	3"

*Minimum surface area needed to mount the product flush with the window frame.