

## Size Specifications

### Minimum Mounting Depth (Inside Mount)

Lift System	Top Treatment Type	Clutch/ Tube Size	Window Depth Min. (Full Inside Mount)	Window Depth Min. (Semi-Inside Mount)
Chain Loop	No Top Treatment	1 1/8"	3 3/8"	2 1/4"
		1 1/4"	3 7/8"	2 1/2"
	Raceway	1 1/8"	3 3/8"	2 1/4"
		1 1/4"	3 7/8"	2 1/4"
	3.5" Fascia	All	3 5/8"	2 1/4"
	4.5" Fascia	1 1/8"	4"	2 1/4"
		1 3/4"	4 1/4"	2 1/4"
	Fabric Valance	1 1/8"	4 1/8"	2 1/4"
		1 3/4"	4 3/8"	2 1/4"
	Wood Valance	1 1/8"	4 3/8"	2 1/4"
1 3/4"		4 5/8"	2 1/4"	
SmartRelease™	Raceway	1 1/4"	3 5/8"	2 1/4"
		2"	3 7/8"	2 1/2"
	3.5" Fascia	1 3/4"	3 5/8"	2 1/4"
	4.5" Fascia	1 3/4"	4 1/8"	2 1/4"
		2"	4 1/4"	2 1/4"
	Fabric Valance	1 3/4"	4 3/8"	2 1/4"
		2"	4 3/8"	2 1/2"
	Wood Valance	1 3/4"	4 1/2"	2 1/4"
2"		4 5/8"	2 1/4"	
Cordless/ Motorization	No Top Treatment	All	3 5/8"	3 1/8"
	Raceway		3 5/8"	2 1/4"
	3.5" Fascia		3 5/8"	2 1/4"
	4.5" Fascia		4 1/8"	2 1/4"
	Fabric Valance		4 3/8"	2 1/4"
	Wood Valance		4 1/2"	2 1/4"
Dual Shade	Raceway	All	3 7/8"	2 1/4"
	Fabric Valance	All	4 1/2"	2 1/4"

- Inside Mount depth may be slightly different depending on the window size and the fabric.
- Clutch sizes depending on the shade width. 1 1/8" clutch: for shades 60" wide or less, 1 3/4" clutch: generally, for shades wider than 60"